

Technical Data Sheet

TUFF Shield Texture Paint (TP)

(previously known as Protective Top Coat (PTC))



USES

- TUFF Render
- TUFFmouldings
- TUFFTEX texture range
- Traditional sand finish plaster
- Painted brickwork
- Concrete walls

TUFF Shield TP is a tintable water resistant high performance top coat suitable over clean & porous masonry & TUFFTEX wall coating systems. TUFF Shield TP works in conjunction with our TUFFWALL & TUFFmouldings range of products.

TUFF Shield TP is a medium-build, high performance coating applied by conventional nap roller or airless spray to form a finishing barrier coat in TUFFTEX's range of systems. Available in Matt sheen level in a wide range of exterior colours. TUFF Shield TP delivers a paint like appearance with film builds twice that of standard exterior paint for enhanced crack hiding performance.

- 10 Year Warranty
- Water Based
- Durable flexible acrylic
- Excellent colour retention
- Easy application and economical clean up.
- Supports adhesion & extends durability of textured coatings
- Ensures consistent appearance and finish of total system.
- Resists pollution, chemical attack and dirt pick-up.
- Easy, safe and economical clean-up

Substrate condition:

All substrate surfaces must be clean sound, dry, cured and free of any dust, dirt mould, fungus, grease or other contaminates. Any loose or damaged substrate must be removed, or patched & repaired and any moisture must also evaporate out prior to TUFF Shield TP being applied onto the substrate.

All surfaces must be clear of efflorescence, grease, oil, mould, dirt, dust, release agents, bond-breakers or other contaminants that may interfere with adhesion. Pre-painted surfaces must be wire brushed or high pressure water blasted to remove loose and cracking paint.

Application:

Brush, Nap Roller or Spray

Sizes:

15Ltr Bucket

Weather Conditions:

If temperatures are less than 8 °C or greater than 30°C, TUFF Shield TP is not recommended to be applied to the substrate.

Freshly applied TUFF Shield TP must be protected from rain, other sources of moisture and frosts for at least 48 hours.

TUFF Shield TP

- Coverage - Approximately 60-80m²
- Wet Film Thickness - 180 microns (approx)
- Dry Film Thickness - 85 microns (approx)
- Shelf Life - A shelf life of 12-24 months is to be expected.
- Product Safety - See MSDS

TUFF Shield TP is classified as non-hazardous according to the criteria of NOHSC.

Not classified as dangerous goods according to the Australian Code for Transport of Dangerous Goods.
NON DANGEROUS GOODS



Manufacturer's Details

TUFFTEX - 3 Hunt Street, Malaga, Western Australia 6090



Telephone +61 8 9248 8788 | info@tufftex.com.au

tufftex.com.au