

Safety Data Sheet

SDS

- COARSE
- SAND
- ATOMIC
- GRAFF
- ROLL ON



TUFFTEX ACRYLIC TEXTURE

IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: TUFFTEX Acrylic Texture
Company: TUFFTEX

Telephone +61 8 9248 8788
Email: info@tufftex.com.au

HAZARDS IDENTIFICATION

Product Name: TUFFTEX (COARSE, SAND, ATOMIC, GRAFF, ROLL ON)
Other Names: None Listed
Product Code: None Listed
UN No: None allocated
Hazchem: None allocated
D.G. Class: None allocated
Pack. Grp.: None allocated
Product Type: Acrylic Emulsion
Major Ingredients: Water based Acrylic- Polymer, Glycol, Inactive Pigments & Aggregates
Poisons Schedule: Not scheduled
Product Use: Trowel-on Acrylic Render

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS Number	Proportion
Water	7732-18-5	10 - 30%
Acrylic Polymer	Proprietary	10 - 30%
Pigments	Proprietary	1 - 30%
Propylene Glycol	57-55-6	1 - 10%
Ingredients not to be hazardous	Proprietary	30 - 80%

OTHER PROPERTIES

Volatile Component: 50%
Auto ignition Temp.: N/Avail
Stability: Stable

HEALTH HAZARD INFORMATION

Primary Routes of Exposure:

Inhalation: Inhalation of vapour can cause headache, nausea, irritation of nose, throat & lungs.
Skin Contact: Prolonged or repeated contact can cause skin irritation.
Eye Contact: Direct contact can cause eye irritation.

FIRST AID INFORMATION

Inhalation: Move subject to fresh air.

Skin Contact: Wash affected areas thoroughly with soap & water. Consult a physician if irritation persists.

Eye Contact: Flush eyes with large amount of water for at least 15 minutes, holding the eye lids apart.
Consult a physician if irritation persists.

Ingestion: If swallowed drink at least 2 glasses of water. Consult a physician.

Toxicity Data: Oral LD 50 (Rat): (Typical) > 5000 mg/kg Dermal LD 50 (Rabbit): > 5000 mg/kg

PERSONAL PROTECTION

Use only in well ventilated areas. Wear protective clothing to minimise skin contact. Where splatter is likely, wear goggles.

FLAMMABILITY

Fire Hazards Material is non flammable

SAFE HANDLING INFORMATION

Storage and Transport

STORAGE: Store in a cool place and out of direct sunlight. Keep containers sealed when not in use.
Store above 4°C and below 50°C

TRANSPORT:

Road and Rail Transport (ACTDG): Class NIL

IATA Classification: Class NIL

Packaging Group: NIL

FIRE FIGHTING INFORMATION

Unusual Hazards: Dried film can burn.

Extinguishing Agents: Use extinguishing media appropriate for surrounding fire.

Storage Requirements: Store out of direct sunlight.

Spills & Clean Up: Contain spills with sand or earth. Remove to suitable container for disposal.
Wash area and equipment with water. Do not allow cleaning water and/or runoffs to enter sewers, storm water or open bodies of water.

PHYSICAL PROPERTIES

Appearance: Heavy Pigmented

Texture Odour: Slight Acrylic/Ammonia

Viscosity: Thixotropic

pH: 9.0 - 10.0

Specific Gravity: 1.5

Flash Point: Non Combustible

Solubility in Water: Dilutable

This SDS has been developed according to Worksafe Australia / NOHSC guidelines.