

SAFETY DATA SHEET

TUFFTEX TUFFSET LIME PUTTY



TUFFTEX TUFFset Lime Putty is hazardous according to health criteria of Safe Work Australia.

Other Names: None Listed
Product Code: None Listed
UN No: None allocated
Hazchem: None allocated
D.G. Class: None allocated
Pack. Grp.: None allocated
Product Type: Lime Finish
Major Ingredients: Slaked lime, acrylic modifiers, Inactive Pigments & Aggregates
Poisons Schedule: Not scheduled
Product Use: Trowel-on lime plaster

IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name:
TUFFTEX TUFFset
Lime Putty

Company:
TUFFTEX
T +61 8 9248 8788
E info@tufftex.com.au

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS Number	Proportion
Calcium Hydroxide	1305-62-0	30-50%
Water	7732-18-5	0-10%
Acrylic Polymer	Proprietary	1-10%
Pigments	Proprietary	1-20%
Ingredients determined not to be hazardous	Proprietary	20-50%

OTHER PROPERTIES

Volatile Component: Not available
Auto ignition Temp: Not available
Stability: Stable

HEALTH HAZARD INFORMATION

Primary Routes of Exposure:

Inhalation: Inhalation of vapour can cause headache, nausea, irritation of nose, throat & lungs.
Skin Contact: Prolonged or repeated contact can cause skin irritation.
Eye Contact: Direct contact can cause eye irritation.

FIRST AID INFORMATION

Inhalation: Move subject to fresh air. Keep at rest until fully recovered. Seek medical advice if effects persist.
Skin Contact: Wash affected areas thoroughly with soap & water. Consult a physician if irritation persists.
Eye Contact: Flush eyes with large amount of water for at least 15 minutes, holding the eye lids apart. Consult a physician if irritation persists.
Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Toxicity Data: Oral LD 50 (Rat): (Typical) > 7250 mg/kg Dermal LD 50 (Rabbit): > 2000 mg/kg

PERSONAL PROTECTION

Use only in well ventilated areas. Wear protective clothing to minimise skin contact. Where splatter is likely, wear goggles.

FLAMMABILITY

Fire Hazards Material is non flammable

SAFE HANDLING INFORMATION

Storage and Transport:

Storage: Store in a cool place and out of direct sunlight. Keep containers sealed when not in use. Store above 4°C and below 40°C

Transport: Road and Rail Transport (ACTDG): Class NIL IATA Classification: Class NIL Packaging Group NIL

FIRE FIGHTING INFORMATION

Extinguishing Agents: Use extinguishing media appropriate for surrounding fire, water fog or fine water spray.

Firefighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing.

Storage Requirements: Store out of direct sunlight.

Spills & Clean Up: Contain spills with sand or earth. Remove to suitable container for disposal. Wash area and equipment with water. Do not allow cleaning water and/or runoffs to enter sewers, storm water or open bodies of water.

PHYSICAL PROPERTIES

Appearance: Paste

Texture Odour: Practically odourless

Viscosity: >14 mm²/s @ 40 degrees C

pH: 11.0 - 12

Specific Gravity: 1.5

Flash Point: Non Combustible

Solubility in Water: Dilutable

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. Current copies are available on the website at tufftex.com.au. This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since TUFFTEX cannot anticipate or control the conditions under which the product may be used, each user prior to usage must review the SDS in the context of how the user intends to handle & use the product in the workplace.